


# VIVA D

## TECHNICAL SPECIFICATIONS



SVL Lighting



- Recessed fixed LED downlight
- Philips LED chip, Osram LED driver
- Simple and elegant appearance
- Soft and tender light perfectly present object without blackspot or dark area
- Module can separate from housing
- Available in various custom outputs
- Opal Diffuser available on request
- Ideal for applications in hospitality, retail, commercial and shop lighting

<b>Dimensions:</b>	D:190mm x H:145mm
<b>Cut out:</b>	170mm
<b>Power Consumption</b>	19W,25W,28W,32W
<b>Finish Colour:</b>	White/Black
<b>CRI:</b>	83 & 90
<b>Colour Temp:</b>	3000K/4000K
<b>Power Factor:</b>	>0.95
<b>Lumens</b>	19W @ 1800lm 25W @ 2400lm 28W @ 2700lm 32W @ 3000lm

Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
VIVD2834W	28W	60D	3000K	W
VIVD2844B	28W	60D	4000K	B
VIVD3234W	33W	60D	3000K	W
VIVD3244B	33W	60D	4000K	B

<b>Beam Angle:</b>	15°,24°,40°,60°
<b>Dimmable:</b>	Leading & Trailing, DALI ,DSI, Touch dim
<b>Life Span:</b>	Up to 50,000 Hrs

\* IES Files are available on request

- Please contact our sales team for specific requirements and order code

### Luminous Intensity Distribution Diagram

