

SQIN D-TW Tunable White



SVL Lighting

TECHNICAL SPECIFICATIONS



OSRAM




- Four square downlight solution to replace CFL and metal halide lighting
- Ideal for applications in hospitality, retail and commercial
- Available with surface mounted case
- OSRAM OT Phase-cut tuneable driver (PC TW)
- OSRAM Prevailed COIN 50 DC COB TW
- Targeting Human Centric Lighting (HCL)
- High flux output up to 1,000 lm
- 5 years warranty on LED

Dimensions:	322mm x 322mm x D206mm
Cut out:	302mm x 302mm
Power Consumption:	4 X 10.1W
Finish Colour:	White, Silver, Black
CRI:	80 / 90
Colour Temp:	2700K - 6500K
Power Factor:	>0.95
Lumens	4 x 910-1020lm @40deg 4 x 865lm-970lm @ 24deg
Beam Angle:	24°,40°
Dimmable:	OT phase-cut TW DIM
Life Span:	50,000 Hrs

* IES Files are available on request

CUT-OUT (mm)



Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
SQIDTW103W	4x10.1W	40°	2700 -6500K	W/S/B
SQIDTW102W	4x10.1W	24°	2700 -6500K	W/S/B