

# OPOL BR

## TECHNICAL SPECIFICATIONS



SVL Lighting



- Recessed LED reflected downlight
- Recessed polycarbonate diffuser offering a low glare symmetrical wide beam distribution with high lumen output
- Die cast aluminium housing
- Adjustable mounting brackets
- Drop glass, square frame option
- Ideal for applications in hospitality, retail and commercial

**Dimensions:** Diameter:195mm x H:78mm

**Cut out:** 170mm

**Power Consumption:** 25W, 27W, 30W

**Finish Colour:** White/Black

**CRI:** 83

**Colour Temp:** 3000K/4000K

**Power Factor:** >0.95

**Lumens**  
 25w @ 2200lm  
 27w @ 2400lm  
 30w @ 2700lm

**Beam Angle:** 60°

**Dimmable:** Leading & Trailing Edge, DALI

**Life Span:** Up to 50,000 Hrs

Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
OPOBR253W	25W	60D	3000K	W
OPOBR254W	25W	60D	4000K	W
OPOBR303W	30W	60D	3000K	W
OPOBR304W	30W	60D	4000K	W

\* Please contact our sales team for specific requirements and order code

\* IES Files are available on request

### Luminous Intensity Distribution Diagram

