

LINO B Surface Mounted



SVL Lighting

TECHNICAL SPECIFICATIONS



OSRAM IP40

- Architecturally designed LED linear profile (68x80mm).
- Comes with polycarbonate opal diffuser and internal reflector for efficient light distribution and uniformity
- High efficiency / quality interconnectable Osram LED Boards used (CRI >90)
- Removable LED Gear Tray for easy installation and maintenance
- Screwless interlocking end caps
- All modules can stand alone or Interconnect for multiple run lengths

Applications:

Decorative Commercial Applications, Boardrooms, Reception Desks, Retail Stores, Residential and Shop lighting & music rooms.

Model:	Surface mounted LED Linear
Dimensions:	68mm (W) x 80mm (H)
Power :	36w/linear mtr
Lumens	122lm/W
Colour Temp:	3000K/4000K
Finish Colour:	White/Black/Silver Custom Powder coat
CRI:	>90
Power Factor:	>0.95
Accessories:	EMERGENCY Kit, Sensors, Joints
Dimming Options:	Trailing edge, 1-10V, DALI Tuneable White

Order Code	wattage	Length	Colour Temp	Trim Color
LINB363W	36W	1160mm	3000K	White

* IES Files are available on request

Please contact our sales team for specific requirements and Order code

L-module



T-module



X-module

