



- Recessed fixed LED downlight
- Philips LED chip, Osram LED driver
- Simple and elegant appearance
- Soft and tender light perfectly present object without blackspot or dark area
- Module can separate from housing
- Available in various custom outputs
- Opal Diffuser available on request
- Ideal for applications in hospitality, retail commercial and shop lighting

Dimensions:	D:165mm x H:140mm
Cut out:	150mm
Power Consumption:	19W,25W,28W,32W
Finish Colour:	White/Black
CRI:	83 & 90
Colour Temp:	3000K/4000K
Power Factor:	>0.95
Lumens	19W @ 1800lm 25W @ 2400lm 28W @ 2700lm 32W @ 3000lm
Beam Angle:	15°,24°,40°,60°
Dimmable:	Leading & Trailing, DALI ,DSI, Touch dim
Life Span:	Up to 50,000 Hrs

Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
VIVC2834W	28W	60D	3000K	W
VIVC2844B	28W	60D	4000K	B
VIVC3234W	33W	60D	3000K	W
VIVC3244B	33W	60D	4000K	B

- Please contact our sales team for specific requirements and order code

* IES Files are available on request

Luminous Intensity Distribution Diagram

