

LUPO A, B



SVL Lighting

TECHNICAL SPECIFICATIONS



OSRAM



IP20

- Recessed fixed downlight
- Deep Conical die cast aluminum housing for low glare
- Recessed polycarbonate diffuser gives a symmetrical wide beam distribution with high lumen output
- Tempered glass providing IP44 protection
- Leading & trailing edge or DALI driver
- Ideal for Foyers, Hotels, Corridors, Function Rooms, Medical and General Lighting
- Available Driver Options:
Tridonic Non-Dimmable Driver,
OSRAM Trailing and Lead edge dimmable driver,
OSRAM DALI Driver

Dimensions: D:140mm x H:105mm
D:165mm x H:114mm

Cut out: 125mm, 150mm

Power Consumption: 19W/23W/26W/33W
(Custom Made)

Finish Colour: White/Black

CRI: 85

Colour Temp: 3000K/4000K

Power Factor: >0.95

Lumens
19w @ 1800lm
23w @ 2200lm
26w @ 2500lm
33w @ 3000lm

Beam Angle: 60° @ D:140mm
70° @ D:165mm

Dimmable: Leading and trailing edge/DALI

Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
LUPA193W	19W	60D	3000K	W
LUPA233W	21W	60D	3000K	W
LUPB264W	26W	70D	4000K	W
LUPD334W	33W	70D	4000K	W

* IES Files are available on request

- Please contact our sales team for specific requirements and all other item codes

