



- Recessed adjustable LED downlight
- 355° rotating and 30° tilt
- Philips LED chip, Osram LED driver
- Simple and elegant appearance
- Soft and tender light perfectly present object without blackspot or dark area
- Module can separate from housing
- Available in various custom outputs
- Opal Diffuser available on request
- Ideal for applications in hospitality, retail, commercial and shop lighting

Dimensions:	D:138mm x H:110mm
Cut out:	125mm
Power Consumption	19W, 25W, 28W, 32W
Finish Colour:	White/Black
CRI:	83 & 90
Colour Temp:	3000K/4000K
Power Factor:	>0.95
Lumens	19W @ 1800lm 25W @ 2400lm 28W @ 2700lm 32W @ 3000lm
Beam Angle:	15°, 24°, 40°, 60°
Dimmable:	Leading & Trailing, DALI, DSI, Touch dim
Life Span:	Up to 50,000 Hrs

* IES Files are available on request

Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
VIVA2834W	28W	60D	3000K	W
VIVA2844B	28W	60D	4000K	B
VIVA3234W	33W	60D	3000K	W
VIVA3244B	33W	60D	4000K	B

- Please contact our sales team for specific requirements and order code

Luminous Intensity Distribution Diagram

