

# SENTO D

## TECHNICAL SPECIFICATIONS



SVL Lighting



- Recessed fixed downlight
- Deep conical housing for low glare
- Minimal trim
- Clear tempered glass
- Leading and trailing edge driver
- CREE COB LED module
- Ideal for applications in foyers, hotels, corridors, function rooms, living area, kitchens

**Dimensions:** 13.5W D:80mm x H:95mm  
18.5W D:80mm x H:120mm

**Cut out:** 70mm

**Power Consumption:** 13.5W  
18.5W

**Finish Colour:** White/Black

**CRI:** 95

**Colour Temp:** 2700K/3000K/4000K

**Power Factor:** >0.9

**Lumens** 950lm  
1600lm

**Beam Angle:** 15°, 25°, 38°, 60°

**Dimmable:** DALI, DSI, TOUCH DIM, 1-10V

*\* IES Files are available on request*

Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
SEND1334W	13.5W	60D	3000K	W
SEND1344W	13.5W	60D	4000K	W
SEND1334B	13.5W	60D	3000K	B
SEND1344B	13.5W	60D	4000K	B

\* Please contact our sales team for specific requirements and order code

### Luminous Intensity Distribution Diagram

