

SQIN C Tunable White

TECHNICAL SPECIFICATIONS



SVL Lighting



OSRAM



- Triple square downlight solution to replace CFL and metal halide lighting
- Ideal for applications in hospitality, retail and commercial
- Available with surface mounted case
- OSRAM OT Phase-cut tunable driver (PC TW)
- OSRAM PrevaLED COIN 50 DC COB TW
- Targeting Human Centric Lighting (HCL)
- High flux output up to 1,000 lm
- 5 years warranty on LED

Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
SQICTW103W	3x10.1W	40°	2700 -6500K	W/S/B
SQICTW102W	3x10.1W	24°	2700 -6500K	W/S/B

Dimensions: 455mm x 175mm x D206mm

Cut out: 435mm x 160mm

Power Consumption: 3 X 10.1W

Finish Colour: White, Silver, Black

CRI: 80 /90

Colour Temp: 2700K - 6500K

Power Factor: >0.95

Lumens 3 x 910-1020lm @40°
3 x 865lm-970lm @ 24°

Beam Angle: 24°,40°

Dimmable: OT phase-cut tunable white
10W driver (PC TW)

Life Span: 50,000 Hrs

** IES Files are available on request*

Product image, mechanical dimensions

