

SENTO SQ Tunable White

TECHNICAL SPECIFICATIONS



SVL Lighting



OSRAM



- Recessed fixed downlight
- Deep conical housing for low glare
- Minimal trim
- Clear tempered glass
- OSRAM OT Phase-cut tunable driver (PC TW)
- OSRAM PrevaLED COIN 50 DC COB TW
- Targeting Human Centric Lighting (HCL)
- High flux output up to 1,000 lm
- Ideal for applications in foyers, hotels, corridors, function rooms, living area, kitchens
- 5 years warranty on LED

Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
SENSTW103W	10.1W	40°	2700 - 6500K	W
SENSTW102W	10.1W	24°	2700 - 6500K	W

Dimensions: 95mm x 95mm

Cut out: 85mm

Power Consumption: 10.1W

Finish Colour: White/Black

CRI: 80 / 90

CCT range: 2700K to 6500K

Power Factor: >0.9

Lumens 910lm – 1020lm @ 40°
865lm – 970lm @ 24°

Beam Angle: 24°, 40°

Dimmable: OT phase-cut tunable white
10W driver (PC TW)

Life Span: 50,000 Hrs

* IES Files are available on request

* Please contact our sales team for specific requirements and ordering codes.

Product image, mechanical dimensions

